

Exhibit 1

US007346472B1

(12) **United States Patent**
Moskowitz et al.(10) **Patent No.:** **US 7,346,472 B1**
(45) **Date of Patent:** **Mar. 18, 2008**(54) **METHOD AND DEVICE FOR MONITORING
AND ANALYZING SIGNALS**(75) Inventors: **Scott A. Moskowitz**, Miami, FL (US);
Michael W. Berry, Albuquerque, NM
(US)(73) Assignee: **Blue Spike, Inc.**, Sunny Isles Beach,
FL (US)(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 722 days.(21) Appl. No.: **09/657,181**(22) Filed: **Sep. 7, 2000**(51) **Int. Cl.**
G06F 19/00 (2006.01)(52) **U.S. Cl.** **702/182; 707/1; 707/2;**
707/3; 707/10; 709/209; 705/51; 380/28(58) **Field of Classification Search** **702/182;**
707/3, 1, 2, 10; 382/100, 232, 282; 380/200,
380/201, 202, 203, 217, 28; 713/176; 709/209;
705/51

See application file for complete search history.

(56) **References Cited****U.S. PATENT DOCUMENTS**

3,947,825 A * 3/1976 Cassada 707/3
 3,984,624 A 10/1976 Waggener
 3,986,624 A 10/1976 Cates, Jr. et al.
 4,038,596 A 7/1977 Lee
 4,200,770 A 4/1980 Hellman et al.
 4,218,582 A 8/1980 Hellman et al.
 4,339,134 A 7/1982 Macheel
 4,405,829 A 9/1983 Rivest et al.
 4,424,414 A 1/1984 Hellman et al.
 4,528,588 A 7/1985 Lofberg
 4,672,605 A 6/1987 Hustig et al.
 4,748,668 A 5/1988 Shamir et al.
 4,789,928 A 12/1988 Fujisaki
 4,827,508 A 5/1989 Shear
 4,876,617 A 10/1989 Best et al.
 4,896,275 A 1/1990 Jackson
 4,908,873 A 3/1990 Philibert et al.
 4,939,515 A 7/1990 Adelson
 4,969,204 A 11/1990 Jones et al.
 4,972,471 A 11/1990 Gross et al.
 4,977,594 A 12/1990 Shear
 4,979,210 A 12/1990 Nagata et al.
 4,980,782 A 12/1990 Ginkel
 5,050,213 A 9/1991 Shear
 5,073,925 A 12/1991 Nagata et al.
 5,077,665 A 12/1991 Silverman et al.
 5,113,437 A 5/1992 Best et al.
 5,136,581 A 8/1992 Muehrcke
 5,161,210 A 11/1992 Druyvesteyn et al.
 5,243,423 A 9/1993 DeJean et al.
 5,243,515 A 9/1993 Lee
 5,287,407 A 2/1994 Holmes
 5,319,735 A 6/1994 Preuss et al.
 5,341,429 A 8/1994 Stringer et al.
 5,341,477 A 8/1994 Pitkin et al.
 5,363,448 A 11/1994 Koopman et al.

5,365,586 A 11/1994 Indeck et al.
 5,369,707 A 11/1994 Follendore, III
 5,379,345 A 1/1995 Greenberg
 5,394,324 A 2/1995 Clearwater
 5,398,285 A 3/1995 Borgelt et al.
 5,406,627 A 4/1995 Thompson et al.
 5,408,505 A 4/1995 Indeck et al.
 5,410,598 A 4/1995 Shear
 5,412,718 A 5/1995 Narasimhalv et al.
 5,418,713 A 5/1995 Allen
 5,428,606 A 6/1995 Moskowitz
 5,450,490 A 9/1995 Jensen et al.
 5,469,536 A 11/1995 Blank
 5,478,990 A 12/1995 Montanari et al.
 5,479,210 A * 12/1995 Cawley et al. 348/390.1
 5,487,168 A 1/1996 Geiner et al.
 5,493,677 A 2/1996 Balogh et al.
 5,497,419 A 3/1996 Hill
 5,506,795 A 4/1996 Yamakawa

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0372601 A1 6/1990
 EP 0565947 A1 10/1993
 EP 0581317 A2 2/1994
 EP 0649261 4/1995
 EP 0651554 A 5/1995

(Continued)

OTHER PUBLICATIONS

Sirbu, M. et al: "Netbill: An Internet Commerce System Optimized for Network Delivered Services," Digest of Papers of the Computer Society Computer Conference (Spring), Mar. 5, 1995, pp. 20-25, vol. CONF. 40, COMPCON, US, Los Alamitos, IEEE Comp. Soc. Press.

Schunter M. et al., "A status report on the SEMPER framework for secure electronic commerce," Computer Networks and ISDN Systems, Sep. 30, 1998, pp. 1501-1510, vol. 30, No. 16-18, NL, North Holland Publishing, Amsterdam.

(Continued)

Primary Examiner—Carol S. W. Tsai(57) **ABSTRACT**

A method and system for monitoring and analyzing at least one signal are disclosed. An abstract of at least one reference signal is generated and stored in a reference database. An abstract of a query signal to be analyzed is then generated so that the abstract of the query signal can be compared to the abstracts stored in the reference database for a match. The method and system may optionally be used to record information about the query signals, the number of matches recorded, and other useful information about the query signals. Moreover, the method by which abstracts are generated can be programmable based upon selectable criteria. The system can also be programmed with error control software so as to avoid the re-occurrence of a query signal that matches more than one signal stored in the reference database.

14 Claims, No Drawings**BLU000001**

US 7,346,472 B1

Page 2

U.S. PATENT DOCUMENTS			
5,513,261 A	4/1996	Maier	5,999,217 A 12/1999 Berners-Lee
5,530,739 A	6/1996	Okada	6,009,176 A 12/1999 Gennaro et al.
5,530,751 A	6/1996	Morris	6,029,126 A * 2/2000 Malvar 704/204
5,530,759 A	6/1996	Braudaway et al.	6,041,316 A 3/2000 Allen
5,539,735 A	7/1996	Moskowitz	6,049,838 A 4/2000 Miller et al.
5,548,579 A	8/1996	Lebrun et al.	6,051,029 A 4/2000 Paterson et al.
5,568,570 A	10/1996	Rabbani	6,061,793 A 5/2000 Tewfik et al.
5,579,124 A	11/1996	Aijala et al.	6,069,914 A 5/2000 Cox
5,581,703 A	12/1996	Baugher et al.	6,078,664 A 6/2000 Moskowitz et al.
5,583,488 A	12/1996	Sala et al.	6,081,251 A 6/2000 Sakai et al.
5,598,470 A	1/1997	Cooper et al.	6,081,597 A 6/2000 Hoffstein et al.
5,606,609 A	2/1997	Houser et al.	6,088,455 A * 7/2000 Logan et al. 380/200
5,613,004 A	3/1997	Cooperman et al.	6,131,162 A 10/2000 Yoshiura et al.
5,617,119 A	4/1997	Briggs et al.	6,141,753 A 10/2000 Zhao et al.
5,625,690 A	4/1997	Michel et al.	6,141,754 A 10/2000 Choy
5,629,980 A	5/1997	Stefik et al.	6,154,571 A 11/2000 Cox et al.
5,633,932 A	5/1997	Davis et al.	6,199,058 B1 3/2001 Wong et al.
5,634,040 A	5/1997	Her et al.	6,205,249 B1 * 3/2001 Moskowitz 382/232
5,636,276 A	6/1997	Brugger	6,208,745 B1 3/2001 Florenio et al.
5,636,292 A	6/1997	Rhoads	6,230,268 B1 5/2001 Miwa et al.
5,640,569 A	6/1997	Miller et al.	6,233,347 B1 5/2001 Chen et al.
5,646,997 A	7/1997	Barton	6,233,684 B1 5/2001 Stefik et al.
5,659,726 A	8/1997	Sandford, II et al.	6,240,121 B1 5/2001 Senoh
5,664,018 A	9/1997	Leighton	6,272,634 B1 8/2001 Tewfik et al.
5,673,316 A	9/1997	Auerbach et al.	6,275,988 B1 8/2001 Nagashima et al.
5,680,462 A	10/1997	Miller et al.	6,278,780 B1 8/2001 Shimada
5,687,236 A	11/1997	Moskowitz et al.	6,278,791 B1 8/2001 Honsinger et al.
5,689,587 A	11/1997	Bender et al.	6,282,300 B1 * 8/2001 Bloom et al. 382/100
5,696,828 A	12/1997	Koopman, Jr.	6,282,650 B1 8/2001 Davis
5,719,937 A	2/1998	Warren et al.	6,285,775 B1 9/2001 Wu et al.
5,721,788 A	2/1998	Powell et al.	6,301,663 B1 10/2001 Kato et al.
5,734,752 A	3/1998	Knox	6,310,962 B1 10/2001 Chung et al.
5,737,416 A	4/1998	Cooper et al.	6,330,335 B1 12/2001 Rhoads
5,737,733 A	4/1998	Eller	6,330,672 B1 12/2001 Shur
5,740,244 A	4/1998	Indeck et al.	6,351,765 B1 2/2002 Pietropaolo et al.
5,745,569 A	4/1998	Moskowitz et al.	6,373,892 B1 4/2002 Ichien et al.
5,748,783 A	5/1998	Rhoads	6,377,625 B1 * 4/2002 Kim 375/240.08
5,751,811 A	5/1998	Magnotti et al.	6,381,618 B1 4/2002 Jones et al.
5,754,697 A *	5/1998	Fu et al. 382/232	6,381,747 B1 4/2002 Wonfor et al.
5,757,923 A	5/1998	Koopman, Jr.	6,385,329 B1 5/2002 Sharma et al.
5,765,152 A	6/1998	Erickson	6,405,203 B1 6/2002 Collart
5,774,452 A	6/1998	Wolosewicz	6,415,041 B1 7/2002 Oami et al.
5,790,677 A	8/1998	Fox et al.	6,425,081 B1 7/2002 Iwamura
5,799,083 A	8/1998	Brothers et al.	6,430,302 B2 * 8/2002 Rhoads 382/100
5,809,139 A	9/1998	Girod et al.	6,442,283 B1 * 8/2002 Tewfik et al. 382/100
5,809,160 A	9/1998	Powell et al.	6,453,252 B1 9/2002 Laroche
5,822,432 A	10/1998	Moskowitz et al.	6,457,058 B1 9/2002 Ullum et al.
5,828,325 A	10/1998	Wolosewicz et al.	6,493,457 B1 12/2002 Quackenbush
5,832,119 A	11/1998	Rhoads	6,522,767 B1 2/2003 Moskowitz et al.
5,848,155 A	12/1998	Cox	6,522,769 B1 2/2003 Rhoads et al.
5,859,920 A	1/1999	Daly et al.	6,523,113 B1 2/2003 Wehrenberg
5,870,474 A	2/1999	Wasilewski et al.	6,530,021 B1 3/2003 Epstein et al.
5,884,033 A	3/1999	Duvall et al.	6,539,475 B1 3/2003 Cox et al.
5,889,868 A	3/1999	Moskowitz et al.	6,557,103 B1 4/2003 Boncelet, Jr. et al.
5,893,067 A	4/1999	Bender et al.	6,584,125 B1 * 6/2003 Katto 370/537
5,894,521 A	4/1999	Conley	6,598,162 B1 7/2003 Moskowitz
5,903,721 A	5/1999	Sixtus	6,606,393 B1 * 8/2003 Xie et al. 382/100
5,905,800 A	5/1999	Moskowitz et al.	6,647,424 B1 11/2003 Pearson et al.
5,905,975 A	5/1999	Ausubel	6,665,489 B2 12/2003 Collart
5,912,972 A	6/1999	Barton	6,668,246 B1 12/2003 Yeung et al.
5,915,027 A	6/1999	Cox et al.	6,687,683 B1 2/2004 Harada et al.
5,917,915 A	6/1999	Hirose	6,725,372 B1 * 4/2004 Lewis et al. 713/176
5,920,900 A	7/1999	Poole et al.	6,754,822 B1 6/2004 Zhao
5,930,369 A	7/1999	Cox et al.	6,775,772 B1 8/2004 Binding et al.
5,930,377 A	7/1999	Powell et al.	6,785,815 B1 8/2004 Serret-Avila et al.
5,940,134 A	8/1999	Wirtz	6,823,455 B1 11/2004 Macy et al.
5,943,422 A	8/1999	Van Wie et al.	6,977,894 B1 12/2005 Achilles et al.
5,963,909 A	10/1999	Warren et al.	6,978,370 B1 12/2005 Kocher
5,973,731 A	10/1999	Schwab	7,043,050 B2 5/2006 Yuval
5,974,141 A	10/1999	Saito	7,058,570 B1 6/2006 Yu et al.
5,991,426 A	11/1999	Cox et al.	2002/0026343 A1 2/2002 Duenke
			2002/0097873 A1 7/2002 Petrovic
			2002/0103883 A1 8/2002 Haverstock et al.

BLU000002

US 7,346,472 B1

Page 3

2003/0126445	A1	7/2003	Wehrenberg
2003/0133702	A1	7/2003	Collart
2004/0037449	A1	2/2004	Davis et al.
2004/0128514	A1	7/2004	Rhoads
2005/0160271	A9	7/2005	Brundage et al.
2006/0005029	A1	1/2006	Petrovic et al.
2006/0013395	A1	1/2006	Brundage et al.

FOREIGN PATENT DOCUMENTS

NL	100523	9/1998
WO	WO 95/14289	5/1995
WO	96/29795	9/1996
WO	97/24833	7/1997
WO	WO 97/44736	11/1997
WO	WO98/37513	8/1998
WO	WO 99/52271	10/1999
WO	WO 99/62044	12/1999
WO	WO 99/63443	12/1999

OTHER PUBLICATIONS

Konrad, K. et al., "Trust and electronic commerce-more than a technical problem," Proceedings of the 18th IEEE Symposium on Reliable Distributed Systems, Proceedings 18th IEEE Symposium on Reliable Distributed Systems, Oct. 19-22, 1999, pp. 360-365, Lausanne, Switzerland.

Kini, A. et al., "Trust in electronic commerce: definition and theoretical considerations," Proceedings of Thirty-first Hawaii International Conference on System Sciences (Cat. No. 98TB100216), Jan. 6-9, 1998, pp. 51-61, Los Alamitos, CA, USA, IEEE Comput. Soc.

Steinauer D.D. et al., "Trust and traceability in electronic commerce," Standard View, Sep. 1997, pp. 118-124, vol. 5, No. 3, ACM, USA.

Moskowitz, Scott, "Bandwidth as Currency," IEEE MultiMedia, Jan.-Mar. 2003, pp. 14-21.

Pending U.S. Appl. No. 08/999,766, filed Jul. 23, 1997, titled "Steganographic Method and Device," assignee Wistaria Trading, Inc.

Pending U.S. Appl. No. 09/456,319, filed Dec. 8, 1999, titled "Transform Implementation of Digital Watermarks," assignee Wistaria Trading, Inc.

Pending U.S. Appl. No. 08/674,726, filed Jul. 2, 1996, titled "Exchange Mechanisms for Digital Information Packages with Bandwidth Securitization, Multichannel Digital Watermarks, and Key Management," assignee Wistaria Trading, Inc.

Pending U.S. Appl. No. 09/545,589, filed Apr. 7, 2000, titled "Method and System for Digital Watermarking," assignee Wistaria Trading, Inc.

Pending U.S. Appl. No. 09/046,627, filed Mar. 24, 1998, titled "Method for Combining Transfer Function with Predetermined Key Creation," inventor: Moskowitz et al.

Pending U.S. Appl. No. 09/594,719, filed Jun. 16, 2000, titled "Utilizing Data Reduction in Steganographic and Cryptographic Systems," inventor: Moskowitz et al.

Pending U.S. Appl. No. 09/731,040, filed Dec. 7, 2000, titled "Systems, Methods and Devices for Trusted Transactions," assignee Blue Spike.

Pending U.S. Appl. No. 10/049,101, filed Feb. 8, 2002, titled "A Secure Personal Content Server," assignee Blue Spike.

Pending U.S. Appl. No. 09/657,181, filed Sep. 7, 2000, titled "Method and Device for Monitoring and Analyzing Signals," assignee Blue Spike.

Pending U.S. Appl. No. 09/671,739, filed Sep. 29, 2000, titled "Method and Device for Monitoring and Analyzing Signals," assignee Blue Spike.

Pending U.S. Appl. No. 09/956,262, filed Sep. 20, 2001, titled "Improved Security Based on Subliminal and Supraliminal Channels for Data Objects," assignee Blue Spike.

Pending U.S. Appl. No. 09/731,039, filed Dec. 7, 2000, titled "System and Method for Permitting Open Access to Data Objects and For Securing Data within the Data Objects," assignee Blue Spike.

Pending U.S. Appl. No. 10/369,344, filed Feb. 18, 2003, titled "Optimization Methods for the Insertion, Protection, and Detection of Digital Watermarks in Digital Data," assignee Wistaria Trading.

Pending U.S. Appl. No. 09/789,711, filed Feb. 22, 2001, titled "Optimization Methods for the Insertion, Protection and Detection of Digital Watermarks," assignee Wistaria Trading.

Pending U.S. Appl. No. 09/644,098, filed Aug. 23, 2000, titled "Multiple Transform Utilization and Application for Secure Digital Watermarking," inventor S. Moskowitz.

Pending U.S. Appl. No. 09/767,733, filed Jan. 24, 2001, titled "Multiple Transform Utilization and Application for Secure Digital Watermarking," inventor S. Moskowitz.

Pending U.S. Appl. No. 10/417,231, filed Apr. 17, 2003, titled "Method, System and Devices for Packet Watermarking and Efficient Provisioning of Bandwidth," inventor S. Moskowitz.

Pending U.S. Appl. No. 09/281,279, filed Mar. 30, 1999, titled "Optimization Methods for the Insertion, Protection, and Detection of Digital Watermarks in Digital Data," inventor S. Moskowitz.

Schneier, Bruce, Applied Cryptography, 2nd Ed., John Wiley & Sons, pp. 9-10, 1996.

Menezes, Alfred J., Handbook of Applied Cryptography, CRC Press, p. 46, 1997.

Merriam-Webster's Collegiate Dictionary, 10th Ed., Merriam Webster, Inc., p. 207.

Brealy, et al., Principles of Corporate Finance, "Appendix A-Using Option Valuation Models", 1984, pp. 448-449.

Copeland, et al., Real Options: A Practitioner's Guide, 2001 pp. 106-107, 201-202, 204-208.

Sarkar, M. "An Assessment of Pricing Mechanisms for the Internet-A Regulatory Imperative", presented MIT Workshop on Internet Economics, Mar. 1995 <http://www.press.vmich.edu/jep/works/SarkAsses.html> on March.

Crawford, D.W. "Pricing Network Usage: A Market for Bandwidth of Market Communication?" presented MIT Workshop on Internet Economics, Mar. 1995 <http://www.press.vmich.edu/jep/works/CrawMarket.html> on March.

Low, S.H., "Equilibrium Allocation and Pricing of Variable Resources Among User-Suppliers", 1988. <http://www.citeseer.nj.nec.com/366503.html>.

Caronni, Germano, "Assuring Ownership Rights for Digital Images", published proceeds of reliable IT systems, v15 '95, H.H. Bruggemann and W Gerhardt-Hackel (Ed.), Viewing Publishing Company, Germany, 1995.

Zhao, Jian. "A WWW Service to Embed and Prove Digital Copyright Watermarks", Proc. of the european conf. on Multimedia Applications, Services & Techniques, Louvain-La-Neuve, Belgium, May 1996.

Gruhl, Daniel et al., Echo Hiding. In Proceeding of the Workshop on Information Hiding. No. 1174 in Lecture Notes in Computer Science. Cambridge, England (May/Jun. 1996).

Oomen, A.W.J. et al., A Variable Bit Rate Buried Data Channel for Compact Disc, J. Audio Eng. Sc., vol. 43, No. 1/2, pp. 23-28 (1995).

Ten Kate, W. et al., A New Surround-Stereo-Surround Coding Techniques, J. Audio Eng. Soc., vol. 40, No. 5, pp. 376-383 (1992).

Gerzon, Michael et al., A High Rate Buried Data Channel for Audio CD, presentation notes, Audio Engineering Soc. 94th Convention (1993).

Sklar, Bernard, Digital Communications, pp. 601-603 (1988).

Jayant, N.S. et al., Digital Coding of Waveforms, Prentice Hall Inc., Englewood Cliffs, NJ, pp. 486-509 (1984).

Bender, Walter R. et al., Techniques for Data Hiding, SPIE Int. Soc. Opt. Eng., vol. 2420, pp. 164-173, 1995.

Zhao, Jian et al., Embedding Robust Labels into Images for Copyright Protection, (xp 000571976), pp. 242-251, 1995.

Menezes, Alfred J., Handbook of Applied Cryptography, CRC Press, p. 175, 1997.

Schneier, Bruce, Applied Cryptography, 1st Ed., pp. 67-68, 1994.

Ten Kate, W. et al., "Digital Audio Carrying Extra Information", IEEE, CH 2847-2/90/0000-1097, (1990).

van Schyndel, et al. A digital Watermark, IEEE Int'l Computer Processing Conference, Austin, TX, Nov. 13-16, 1994, pp. 86-90.

BLU000003

US 7,346,472 B1

Page 4

- Smith, et al. Modulation and Information Hiding in Images, Springer Verlag, 1st Int'l Workshop, Cambridge, UK, May 30-Jun. 1, 1996, pp. 207-227.
- Kutter, Martin et al., Digital Signature of Color Images Using Amplitude Modulation, SPIE-E197, vol. 3022, pp. 518-527.
- Puate, Joan et al., Using Fractal Compression Scheme to Embed a Digital Signature into an Image, SPIE-96 Proceedings, vol. 2915, Mar. 1997, pp. 108-118.
- Swanson, Mitchell D., et al., Transparent Robust Image Watermarking, Proc. of the 1996 IEEE Int'l Conf. on Image Processing, vol. 111, 1996, pp. 211-214.
- Swanson, Mitchell D., et al. Robust Data Hiding for Images, 7th IEEE Digital Signal Processing Workshop, Leon, Norway. Sep. 1-4, 1996, pp. 37-40.
- Zhao, Jian et al., Embedding Robust Labels into Images for Copyright Protection, Proceeding of the Know Right '95 Conference, pp. 242-251.
- Koch, E., et al., Towards Robust and Hidden Image Copyright Labeling, 1995 IEEE Workshop on Nonlinear Signal and Image Processing, Jun. 1995 Neos Marmaras pp. 4.
- Van Schyndel, et al., Towards a Robust Digital Watermark, Second Asain Image Processing Conference, Dec. 6-8, 1995, Singapore, vol. 2, pp. 504-508.
- Tirkel, A.Z., A Two-Dimensional Digital Watermark, DICTA '95, Univ. of Queensland, Brisbane, Dec. 5-8, 1995, pp. 7.
- Tirkel, A.Z., Image Watermarking-A Spread Spectrum Application, ISSSTA '96, Sep. 1996, Mainz, German, pp. 6.
- O'Ruanaidh, et al. Watermarking Digital Images for Copyright Protection, IEEE Proceedings, vol. 143, No. 4, Aug. 96, pp. 250-256.
- Cox, et al., Secure Spread Spectrum Watermarking for Multimedia, NEC Research Institute, Techinal Report 95-10, pp. 33.
- Kahn, D., The Code Breakers, The MacMillan Company, 1969, pp. xIII, 81-83, 513, 515, 522-526, 863.
- Boney, et al., Digital Watermarks for Audio Signals, EVSIPCO, 96, pp. 473-480.
- Dept. of Electrical Engineering, Del Ft University of Technology, Del ft The Netherlands, Cr.C. Langelaar et al., Copy Protection for Multimedia Data based on Labeling Techniques, Jul. 1996 9 pp.
- F. Hartung, et al., Digital Watermarking of Raw and Compressed Video, SPIE vol. 2952, pp. 205-213.
- Craver, et al., Can Invisible Watermarks Resolve Rightful Ownerships? IBM Research Report, RC 20509 (Jul. 25, 1996) 21 pp.
- Press, et al., Numerical Recipes In C, Cambridge Univ. Press, 1988, pp. 398-417.
- Pohlmann, Ken C., Principles of Digital Audio, 3rd Ed., 1995, pp. 32-37, 40-48, 138, 147-149, 332, 333, 364, 499-501, 508-509, 564-571.
- Pohlmann, Ken C., Principles of Digital Audio, 2nd Ed., 1991, pp. 1-9, 19-25, 30-33, 41-48, 54-57, 86-107, 375-387.
- Schneier, Bruce, Applied Cryptography, John Wiley & Sons, inc., New York, 1994, pp. 68, 69, 387-392, 1-57, 273-275, 321-324.
- Boney, et al., Digital Watermarks for Audio Signals, Proceedings of the International Conf. on Multimedia Computing and Systems, Jun. 17-23, 1996, Hiroshima Japan 0-8186-7436-9 196, pp. 473-480.
- Johnson, et al., Transform Permuted Watermarking for Copyright Protection of Digital Video, IEEE Globecom 1998, Nov. 8-12, 1998, New York New York vol. 2 1998 pp. 684-689 (ISBN 0-7803-4985-7).
- Rivest, et al., "Pay Word and Micromint: Two Simple Micropayment Schemes," MIT Laboratory for Computer Science, Cambridge, MA, May 7, 1996 pp. 1-18.
- Bender, et al., Techniques for Data Hiding, IBM Systems Journal, vol. 35, Nos. 3 & 4, 1996, pp. 313-336.
- Moskowitz, Bandwith as Currency, IEEE Multimedia, Jan.-Mar. 2003, pp. 14-21.
- Moskowitz, Multimedia Security Technologies for Digital Rights Management, 2006, Academic Press, "Introduction-Digital Rights Management" pp. 3-22.
- Rivest, et al., "Pay Word and MicroMint: Two Simple Micropayment Schemes" Mir Laboratory for Computer Science, Cambridge, MA, Apr. 27, 2001, pp. 1-18.
- Tomsich, et al., "Towards a secure and de-centralized digital watermarking infrastructure for the protection of Intellectual Property", in Electronic Commerce and Web Technologies, Proceedings (ECWEB).
- Moskowitz, "What is Acceptable Quality in the Application of Digital Watermarking: Trade-offs of Security, Robustness and Quality", IEEE Computer Society Proceedings of ITCC 2002 Apr. 10, 2002 pp. 80-84.
- Lemma, et al. "Secure Watermark Embedding through Partial Encryption", International Workshop on Digital Watermarking ("IWDW" 2006), Springer Lecture Notes in Computer Science 2006, (to appear) 13.
- Kocher, et al., "Self Protecting Digital Content", Technical Report from the CRI Content Security Research Initiative, Cryptography Research, Inc. 2002-2003 14 pages.
- Sirbu, M. et al., "Net Bill: An Internet Commerce System Optimized for Network Delivered Services", Digest of Papers of the Computer Society Computer Conference (Spring) Mar. 5, 1995 pp. 20-25 vol. CONF40.
- Schunter, M. et al., "A Status Report on the SEMPER framework for Secure Electronic Commerce", Computer Networks and ISDN Systems, Sep. 30, 1998 pp. 1501-1510 vol. 30, No. 16-18 NL North Holland.
- Konrad, K. et al., "Trust and Elecronic Commerce-more than a techinal problem," Proceedings of the 18th IEEE Symposium on Reliable Distributed Systems Oct. 19-22, 1999 pp. 360-365 Lausanne.
- Kini, a. et al., "Trust in Electronic Commerce: Definition and Theoretical Considerations", Proceedings of the 31st Hawaii Int'l Conf. on System Sciences (Cat. No. 98TB100216), Jan. 6-9, 1998, pp. 51-61, Los.
- Steinauer D. D., et al., "Trust and Traceability in Electronic Commerce", Standard View, Sep. 1997, pp. 118-124, vol. 5 No. 3, ACM, USA.
- Hartung, et al. "Multimedia Watermarking Techniques", Proceedings of the IEEE, Special Issue, Identification & Protection of Multimedia Information, pp. 1079-1107 Jul. 1999 vol. 87 No. 7 IEEE.

* cited by examiner

BLU000004

US 7,346,472 B1

1

**METHOD AND DEVICE FOR MONITORING
AND ANALYZING SIGNALS****CROSS-REFERENCE TO RELATED
APPLICATIONS**

This application claims the benefit of pending U.S. patent application Ser. No. 08/999,766, filed Jul. 23, 1997, entitled "Steganographic Method and Device"; pending U.S. patent application Ser. No. 08/772,222, filed Dec. 20, 1996, entitled "Z-Transform Implementation of Digital Watermarks"; pending U.S. patent application Ser. No. 09/456,319, filed Dec. 8, 1999, entitled "Transform Implementation of Digital Watermarks"; pending U.S. patent application Ser. No. 08/674,726, filed Jul. 2, 1996, entitled "Exchange Mechanisms for Digital Information Packages with Bandwidth Securitization, Multichannel Digital Watermarks, and Key Management"; pending U.S. patent application Ser. No. 09/545,589, filed Apr. 7, 2000, entitled "Method and System for Digital Watermarking"; pending U.S. patent application Ser. No. 09/046,627, filed Mar. 24, 1998, entitled "Method for Combining Transfer Function with Predetermined Key Creation"; pending U.S. patent application Ser. No. 09/053,628, filed Apr. 2, 1998, entitled "Multiple Transform Utilization and Application for Secure Digital Watermarking"; pending U.S. patent application Ser. No. 09/281,279, filed Mar. 30, 1999, entitled "Optimization Methods for the Insertion, Protection, and Detection . . ."; U.S. patent application Ser. No. 09/594,719, filed Jun. 16, 2000, entitled "Utilizing Data Reduction in Steganographic and Cryptographic Systems" (which is a continuation-in-part of PCT application No. PCT/US00/06522, filed Mar. 14, 2000, which PCT application claimed priority to U.S. Provisional Application No. 60/125,990, filed Mar. 24, 1999); now abandoned U.S. Application No. 60/169,274, filed Dec. 7, 1999, entitled "Systems, Methods And Devices For Trusted Transactions"; and PCT Application No. PCT/US00/21189, filed Aug. 4, 2000 (which claims priority to U.S. Patent Application Ser. No. 60/147,134, filed Aug. 4, 1999, and to U.S. Patent Application No. 60/213,489, filed Jun. 23, 2000, both of which are entitled, "A Secure Personal Content Server"). The previously identified patents and/or patent applications are hereby incorporated by reference, in their entireties.

In addition, this application hereby incorporates by reference, as if fully stated herein, the total disclosures of U.S. Pat. No. 5,613,004 "Steganographic Method and Device"; U.S. Pat. No. 5,745,569 "Method for Stega-Cipher Protection of Computer Code"; and U.S. Pat. No. 5,889,868 "Optimization Methods for the Insertion, Protection, and Detection of Digital Watermarks in Digitized Data."

BACKGROUND OF THE INVENTION**1. Field of the Invention**

The invention relates to the monitoring and analysis of digital information. A method and device are described which relate to signal recognition to enhance identification and monitoring activities.

2. Description of the Related Art

Many methods and protocols are known for transmitting data in digital form for multimedia applications (including computer applications delivered over public networks such as the internet or World Wide Web ("WWW")). These methods may include protocols for the compression of data, such that it may more readily and quickly be delivered over limited bandwidth data lines. Among standard protocols for

2

data compression of digital files may be mentioned the MPEG compression standards for audio and video digital compression, promulgated by the Moving Picture Experts Group. Numerous standard reference works and patents discuss such compression and transmission standards for digitized information.

Digital watermarks help to authenticate the content of digitized multimedia information, and can also discourage piracy. Because piracy is clearly a disincentive to the digital distribution of copyrighted content, establishment of responsibility for copies and derivative copies of such works is invaluable. In considering the various forms of multimedia content, whether "master," stereo, NTSC video, audio tape or compact disc, tolerance of quality will vary with individuals and affect the underlying commercial and aesthetic value of the content. It is desirable to tie copyrights, ownership rights, purchaser information or some combination of these and related data into the content in such a manner that the content must undergo damage, and therefore reduction of its value, with subsequent, unauthorized distribution, commercial or otherwise. Digital watermarks address many of these concerns. A general discussion of digital watermarking as it has been applied in the art may be found in U.S. Pat. No. 5,687,236 (whose specification is incorporated in whole herein by reference).

Further applications of basic digital watermarking functionality have also been developed. Examples of such applications are shown in U.S. Pat. No. 5,889,868 (whose specification is incorporated in whole herein by reference). Such applications have been drawn, for instance, to implementations of digital watermarks that were deemed most suited to particular transmissions, or particular distribution and storage mediums, given the nature of digitally sampled audio, video, and other multimedia works. There have also been developed techniques for adapting watermark application parameters to the individual characteristics of a given digital sample stream, and for implementation of digital watermarks that are feature-based—i.e., a system in which watermark information is not carried in individual samples, but is carried in the relationships between multiple samples, such as in a waveform shape. For instance, natural extensions may be added to digital watermarks that may also separate frequencies (color or audio), channels in 3D while utilizing discreteness in feature-based encoding only known to those with pseudo-random keys (i.e., cryptographic keys) or possibly tools to access such information, which may one day exist on a quantum level.

A matter of general weakness in digital watermark technology relates directly to the manner of implementation of the watermark. Many approaches to digital watermarking leave detection and decode control with the implementing party of the digital watermark, not the creator of the work to be protected. This weakness removes proper economic incentives for improvement of the technology. One specific form of exploitation mostly regards efforts to obscure subsequent watermark detection. Others regard successful over encoding using the same watermarking process at a subsequent time. Yet another way to perform secure digital watermark implementation is through "key-based" approaches.

SUMMARY OF THE INVENTION

A method for monitoring and analyzing at least one signal is disclosed, which method comprises the steps of: receiving at least one reference signal to be monitored; creating an abstract of the at least one reference signal; storing the

BLU000005

US 7,346,472 B1

3

abstract of the at least one reference signal in a reference database; receiving at least one query signal to be analyzed; creating an abstract of the at least one query signal; and comparing the abstract of the at least one query signal to the abstract of the at least one reference signal to determine if the abstract of the at least one query signal matches the abstract of the at least one reference signal.

A method for monitoring a plurality of reference signals is also disclosed, which method comprises the steps of: creating an abstract for each one of a plurality of reference signals; storing each of the abstracts in a reference database; receiving at least one query signal to be analyzed; creating an abstract of each at least one query signal; locating an abstract in the reference database that matches the abstract of each at least one query signal; and recording the identify of the reference signal whose abstract matched the abstract of each at least one query signal.

A computerized system for monitoring and analyzing at least one signal is also disclosed, which system comprises: a processor for creating an abstract of a signal using selectable criteria; a first input for receiving at least one reference signal to be monitored, the first input being coupled to the processor such that the processor may generate an abstract for each reference signal input to the processor; a reference database, coupled to the processor, for storing abstracts of each at least one reference signal; a second input for receiving at least one query signal to be analyzed, the second input being coupled to the processor such that the processor may generate an abstract for each query signal; and a comparing device, coupled to the reference database and to the second input, for comparing an abstract of the at least one query signal to the abstracts stored in the reference database to determine if the abstract of the at least one query signal matches any of the stored abstracts.

Further, an electronic system for monitoring and analyzing at least one signal is disclosed, which system comprises: a first input for receiving at least one reference signal to be monitored, a first processor for creating an abstract of each reference signal input to the first processor through the first input; a second input for receiving at least one query signal to be analyzed, a second processor for creating an abstract of each query signal; a reference database for storing abstracts of each at least one reference signal; and a comparing device for comparing an abstract of the at least one query signal to the abstracts stored in the reference database to determine if the abstract of the at least one query signal matches any of the stored abstracts.

DETAILED DESCRIPTION OF THE INVENTION

While there are many approaches to data reduction that can be utilized, a primary concern is the ability to reduce the digital signal in such a manner as to retain a "perceptual relationship" between the original signal and its data reduced version. This relationship may either be mathematically discernible or a result of market-dictated needs. The purpose is to afford a more consistent means for classifying signals than proprietary, related text-based approaches. A simple analogy is the way in which a forensic investigator uses a sketch artist to assist in determining the identity of a human.

In one embodiment of the invention, the abstract of a signal may be generated by the following steps: 1) analyze the characteristics of each signal in a group of audible/perceptible variations for the same signal (e.g., analyze each of five versions of the same song—which versions may have

4

the same lyrics and music but which are sung by different artists); and 2) select those characteristics which achieve remain relatively constant (or in other words, which have minimum variation) for each of the signals in the group. Optionally, the null case may be defined using those characteristics which are common to each member of the group of versions.

Lossless and lossy compression schemes are appropriate candidates for data reduction technologies, as are those subset of approaches that are based on perceptual models, such as AAC, MP3, TwinVQ, JPEG, GIF, MPEG, etc. Where spectral transforms fail to assist in greater data reduction of the signal, other signal characteristics can be identified as candidates for further data reduction. Linear predictive coding (LPC), z-transform analysis, root mean square (rms), signal to peak, may be appropriate tools to measure signal characteristics, but other approaches or combinations of signal characteristic analysis are contemplated. While such signal characteristics may assist in determining particular applications of the present invention, a generalized approach to signal recognition is necessary to optimize the deployment and use of the present invention.

Increasingly, valuable information is being created and stored in digital form. For example, music, photographs and motion pictures can all be stored and transmitted as a series of binary digits—1's and 0's. Digital techniques permit the original information to be duplicated repeatedly with perfect or near perfect accuracy, and each copy is perceived by viewers or listeners as indistinguishable from the original signal. Unfortunately, digital techniques also permit the information to be easily copied without the owner's permission. While digital representations of analog waveforms may be analyzed by perceptually-based or perceptually-limited analysis it is usually costly and time-consuming to model the processes of the highly effective ability of humans to identify and recognize a signal. In those applications where analog signals require analysis, the cost of digitizing the analog signal is minimal when compared to the benefits of increased accuracy and speed of signal analysis and monitoring when the processes contemplated by this invention are utilized.

The present invention relates to identification of digitally-sampled information, such as images, audio and video. Traditional methods of identification and monitoring of those signals do not rely on "perceptual quality," but rather upon a separate and additional signal. Within this application, such signals will be called "additive signals" as they provide information about the original images, audio or video, but such information is in addition to the original signal. One traditional, text-based additive signal is title and author information. The title and author, for example, is information about a book, but it is in addition to the text of the book. If a book is being duplicated digitally, the title and author could provide one means of monitoring the number of times the text is being duplicated, for example, through an Internet download. The present invention, however, is directed to the identification of a digital signal—whether text, audio, or video—using only the digital signal itself and then monitoring the number of times the signal is duplicated. Reliance on an additive signal has many shortcomings. For example, first, someone must incorporate the additive signal within the digital data being transmitted, for example, by concatenation or through an embedding process. Such an additive signal, however, can be easily identified and removed by one who wants to utilize the original signal without paying for its usage. If the original signal itself is used to identify the content, an unauthorized user could not

BLU000006

US 7,346,472 B1

5

avoid payment of a royalty simply by removing the additive signal—because there is no additive signal to remove. Hence, the present invention avoids a major disadvantage of the prior art.

One such additive signal that may be utilized is a digital watermark—which ideally cannot be removed without perceptually altering the original signal. A watermark may also be used as a monitoring signal (for example, by encoding an identifier that uniquely identifies the original digital signal into which the identifier is being embedded). A digital watermark used for monitoring is also an additive signal, and such a signal may make it difficult for the user who wants to duplicate a signal without paying a royalty—mainly by degrading the perceptual quality of the original signal if the watermark (and hence the additive monitoring signal) is removed. This is, however, is a different solution to the problem.

The present invention eliminates the need of any additive monitoring signal because the present invention utilizes the underlying content signal as the identifier itself. Nevertheless, the watermark may increase the value of monitoring techniques by increasing the integrity of the embedded data and by indicating tampering of either the original content signal or the monitoring signal. Moreover, the design of a watermarking embedding algorithm is closely related to the perceptibility of noise in any given signal and can represent an ideal subset of the original signal: the watermark bits are an inverse of the signal to the extent that lossy compression schemes, which can be used, for instance, to optimize a watermarking embedding scheme, can yield information about the extent to which a data signal can be compressed while holding steadfast to the design requirement that the compressed signal maintain its perceptual relationship with the original, uncompressed signal. By describing those bits that are candidates for imperceptible embedding of watermark bits, further data reduction may be applied on the candidate watermarks as an example of retaining a logical and perceptible relationship with the original uncompressed signal.

Of course, the present invention may be used in conjunction with watermarking technology (including the use of keys to accomplish secure digital watermarking), but watermarking is not necessary to practice the present invention. Keys for watermarking may have many forms, including: descriptions of the original carrier file formatting, mapping of embedded data (actually imperceptible changes made to the carrier signal and referenced to the predetermined key or key pairs), assisting in establishing the watermark message data integrity (by incorporation of special one way functions in the watermark message data or key), etc. Discussions of these systems in the patents and pending patent applications are incorporated by reference above. The “recognition” of a particular signal or an instance of its transmission, and its monitoring are operations that may be optimized through the use of digital watermark analysis.

A practical difference between the two approaches of using a separate, additive monitoring signal and using the original signal itself as the monitoring signal is control. If a separate signal is used for monitoring, then the originator of the text, audio or video signal being transmitted and the entity doing the monitoring have to agree as to the nature of the separate signal to be used for monitoring—otherwise, the entity doing the monitoring would not know where to look, for what to look, or how to interpret the monitoring signal once it was identified and detected. On the other hand, if the original signal is used itself as a monitoring signal, then no such agreement is necessary. Moreover, a more

6

logical and self-sufficient relationship between the original and its data-reduced abstract enhances the transparency of any resulting monitoring efforts. The entity doing the monitoring is not looking for a separate, additive monitoring system, and further, need not have to interpret the content of the monitoring signal.

Monitoring implementations can be handled by robust watermark techniques (those techniques that are able to survive many signal manipulations but are not inherently “secure” for verification of a carrier signal absent a logically-related watermarking key) and forensic watermark techniques (which enable embedding of watermarks that are not able to survive perceptible alteration of the carrier signal and thus enable detection of tampering with the originally watermarked carrier signal). The techniques have obvious trade-offs between speed, performance and security of the embedded watermark data.

In other disclosures, we suggest improvements and implementations that relate to digital watermarks in particular and embedded signaling in general. A digital watermark may be used to “tag” content in a manner that is not humanly-perceptible, in order to ensure that the human perception of the signal quality is maintained. Watermarking, however, must inherently alter at least one data bit of the original signal to represent a minimal change from the original signal’s “unwatermarked state.” The changes may affect only a bit, at the very least, or be dependent on information hiding relating to signal characteristics, such as phase information, differences between digitized samples, root mean square (RMS) calculations, z-transform analysis, or similar signal characteristic category.

There are weaknesses in using digital watermark technology for monitoring purposes. One weakness relates directly to the way in which watermarks are implemented. Often, the persons responsible for encoding and decoding the digital watermark are not the creator of the valuable work to be protected. As such, the creator has no input on the placement of the monitoring signal within the valuable work being protected. Hence, if a user wishing to avoid payment of the royalty can find a way to decode or remove the watermark, or at least the monitoring signal embedded in the watermark, then the unauthorized user may successfully duplicate the signal with impunity. This could occur, for example, if either of the persons responsible for encoding or decoding were to have their security compromised such that the encoding or decoding algorithms were discovered by the unauthorized user.

With the present invention, no such disadvantages exist because the creator need not rely on anyone to insert a monitoring signal—as no such signal is necessary. Instead, the creator’s work itself is used as the monitoring signal. Accordingly, the value in the signal will have a strong relationship with its recognizability.

By way of improving methods for efficient monitoring as well as effective confirmation of the identity of a digitally-sampled signal, the present invention describes useful methods for using digital signal processing for benchmarking a novel basis for differencing signals with binary data comparisons. These techniques may be complemented with perceptual techniques, but are intended to leverage the generally decreasing cost of bandwidth and signal processing power in an age of increasing availability and exchange of digitized binary data.

So long as there exist computationally inexpensive ways of identifying an entire signal with some fractional representation or relationship with the original signal, or its perceptually observable representation, we envision meth-

BLU000007

US 7,346,472 B1

7

ods for faster and more accurate auditing of signals as they are played, distributed or otherwise shared amongst providers (transmitters) and consumers (receivers). The ability to massively compress a signal to its essence—which is not strictly equivalent to “lossy” or “lossless” compression schemes or perceptual coding techniques, but designed to preserve some underlying “aesthetic quality” of the signal—represents a useful means for signal analysis in a wide variety of applications. The signal analysis, however, must maintain the ability to distinguish the perceptual quality of the signals being compared. For example, a method which analyzed a portion of a song by compressing it to a single line of lyrics fails to maintain the ability to distinguish the perceptual quality of the songs being compared. Specifically, for example, if the song “New York State of Mind” were compressed to the lyrics “I’m in a New York State of Mind,” such a compression fails to maintain the ability to distinguish between the various recorded versions of the song, say, for example between Billy Joel’s recording and Barbara Streisand’s recording. Such a method is, therefore, incapable of providing accurate monitoring of the artist’s recordings because it could not determine which of the two artists is deserving of a royalty—unless of course, there is a separate monitoring signal to provide the name of the artist or other information sufficient to distinguish the two versions. The present invention, however, aims to maintain some level of perceptual quality of the signals being compared and would deem such a compression to be excessive.

This analogy can be made clearer if it is understood that there are a large number of approaches to compressing a signal to, say, $1/10,000^{th}$ of its original size, not for maintaining its signal quality to ensure computational ease for commercial quality distribution, but to assist in identification, analysis or monitoring of the signal. Most compression is either lossy or lossless and is designed with psychoacoustic or psychovisual parameters. That is to say, the signal is compressed to retain what is “humanly-perceptible.” As long as the compression successfully mimics human perception, data space may be saved when the compressed file is compared to the uncompressed or original file. While psychoacoustic and psychovisual compression has some relevance to the present invention, additional data reduction or massive compression is anticipated by the present invention. It is anticipated that the original signal may be compressed to create a realistic or self-similar representation of the original signal, so that the compressed signal can be referenced at a subsequent time as unique binary data that has computational relevance to the original signal. Depending on the application, general data reduction of the original signal can be as simple as massive compression or may relate to the watermark encoding envelope parameter (those bits which a watermarking encoding algorithm deem as candidate bits for mapping independent data or those bits deemed imperceptible to human senses but detectable to a watermark detection algorithm). In this manner, certain media which are commonly known by signal characteristics, a painting, a song, a TV commercial, a dialect, etc., may be analyzed more accurately, and perhaps, more efficiently than a text-based descriptor of the signal. So long as the sender and receiver agree that the data representation is accurate, even insofar as the data-reduction technique has logical relationships with the perceptibility of the original signal, as they must with commonly agreed to text descriptors, no independent cataloging is necessary.

The present invention generally contemplates a signal recognition system that has at least five elements. The actual number of elements may vary depending on the number of

8

domains in which a signal resides (for example, audio is at least one domain while visual carriers are at least two dimensional). The present invention contemplates that the number of elements will be sufficient to effectively and efficiently meet the demands of various classes of signal recognition. The design of the signal recognition that may be used with data reduction is better understood in the context of the general requirements of a pattern or signal recognition system.

The first element is the reference database, which contains information about a plurality of potential signals that will be monitored. In one form, the reference database would contain digital copies of original works of art as they are recorded by the various artists, for example, contain digital copies of all songs that will be played by a particular radio station. In another form, the reference database would contain not perfect digital copies of original works of art, but digital copies of abstracted works of art, for example, contain digital copies of all songs that have been preprocessed such that the copies represent the perceptual characteristics of the original songs. In another form, the reference database would contain digital copies of processed data files, which files represent works of art that have been preprocessed in such a fashion as to identify those perceptual differences that can differentiate one version of a work of art from another version of the same work of art, such as two or more versions of the same song, but by different artists. These examples have obvious application to visually communicated works such as images, trademarks or photographs, and video as well.

The second element is the object locator, which is able to segment a portion of a signal being monitored for analysis (i.e., the “monitored signal”). The segmented portion is also referred to as an “object.” As such, the signal being monitored may be thought of comprising a set of objects. A song recording, for example, can be thought of as having a multitude of objects. The objects need not be of uniform length, size, or content, but merely be a sample of the signal being monitored. Visually communicated informational signals have related objects; color and size are examples.

The third element is the feature selector, which is able to analyze a selected object and identify perceptual features of the object that can be used to uniquely describe the selected object. Ideally, the feature selector can identify all, or nearly all, of the perceptual qualities of the object that differentiate it from a similarly selected object of other signals. Simply, a feature selector has a direct relationship with the perceptibility of features commonly observed. Counterfeiting is an activity which specifically seeks out features to misrepresent the authenticity of any given object. Highly granular, and arguably successful, counterfeiting is typically sought for objects that are easily recognizable and valuable, for example, currency, stamps, and trademarked or copyrighted works and objects that have value to a body politic.

The fourth element is the comparing device which is able to compare the selected object using the features selected by the feature selector to the plurality of signals in the reference database to identify which of the signals matches the monitored signal. Depending upon how the information of the plurality of signals is stored in the reference database and depending upon the available computational capacity (e.g., speed and efficiency), the exact nature of the comparison will vary. For example, the comparing device may compare the selected object directly to the signal information stored in the database. Alternatively, the comparing device may need to process the signal information stored in the database using input from the feature selector and then compare the

BLU000008

US 7,346,472 B1

9

selected object to the processed signal information. Alternatively, the comparing device may need to process the selected object using input from the feature selector and then compare the processed selected object to the signal information. Alternatively, the comparing device may need to process the signal information stored in the database using input from the feature selector, process the selected object using input from the feature selector, and then compare the processed selected object to the processed signal information.

The fifth element is the recorder which records information about the number of times a given signal is analyzed and detected. The recorder may comprise a database which keeps track of the number of times a song, image, or a movie has been played, or may generate a serial output which can be subsequently processed to determine the total number of times various signals have been detected.

Other elements may be added to the system or incorporated into the five elements identified above. For example, an error handler may be incorporated into the comparing device. If the comparing device identifies multiple signals which appear to contain the object being sought for analysis or monitoring, the error handler may offer further processing in order to identify additional qualities or features in the selected object such that only one of the set of captured signals is found to contain the further analyzed selected object that actually conforms with the object thought to have been transmitted or distributed.

Moreover, one or more of the five identified elements may be implemented with software that runs on the same processor, or which uses multiple processors. In addition, the elements may incorporate dynamic approaches that utilize stochastic, heuristic, or experience-based adjustments to refine the signal analysis being conducted within the system, including, for example, the signal analyses being performed within the feature selector and the comparing device. This additional analyses may be viewed as filters that are designed to meet the expectations of accuracy or speed for any intended application.

Since maintenance of original signal quality is not required by the present invention, increased efficiencies in processing and identification of signals can be achieved. The present invention concerns itself with perceptible relationships only to the extent that efficiencies can be achieved both in accuracy and speed with enabling logical relationships between an original signal and its abstract.

The challenge is to maximize the ability to sufficiently compress a signal to both retain its relationship with the original signal while reducing the data overhead to enable more efficient analysis, archiving and monitoring of these signals. In some cases, data reduction alone will not suffice: the sender and receiver must agree to the accuracy of the recognition. In other cases, agreement will actually depend on a third party who authored or created the signal in question. A digitized signal may have parameters to assist in establishing more accurate identification, for example, a "signal abstract" which naturally, or by agreement with the creator, the copyright owner or other interested parties, can be used to describe the original signal. By utilizing less than the original signal, a computationally inexpensive means of identification can be used. As long as a realistic set of conditions can be arrived at governing the relationship between a signal and its data reduced abstract, increases in effective monitoring and transparency of information data flow across communications channels is likely to result. This feature is significant in that it represents an improvement over how a digitally-sampled signal can be cataloged and

10

identified, though the use of a means that is specifically selected based upon the strengths of a general computing device and the economic needs of a particular market for the digitized information data being monitored. The additional benefit is a more open means to uniformly catalog, analyze, and monitor signals. As well, such benefits can exist for third parties, who have a significant interest in the signal but are not the sender or receiver of said information.

As a general improvement over the art, the present invention incorporates what could best be described as "computer-acoustic" and "computer-visual" modeling, where the signal abstracts are created using data reduction techniques to determine the smallest amount of data, at least a single bit, which can represent and differentiate two digitized signal representations for a given predefined signal set. Each of such representations must have at least a one bit difference with all other members of the database to differentiate each such representation from the others in the database. The predefined signal set is the object being analyzed. The signal identifier/detector should receive its parameters from a database engine. The engine will identify those characteristics (for example, the differences) that can be used to distinguish one digital signal from all other digital signals that are stored in its collection. For those digital signals or objects which are seemingly identical, excepting that the signal may have different performance or utilization in the newly created object, benefits over additive or text-based identifiers are achieved. Additionally, decisions regarding the success or failure of an accurate detection of any given object may be flexibly implemented or changed to reflect market-based demands of the engine. Appropriate examples are songs or works or art which have been sampled or re-produced by others who are not the original creator.

In some cases, the engine will also consider the NULL case for a generalized item not in its database, or perhaps in situations where data objects may have collisions. For some applications, the NULL case is not necessary, thus making the whole system faster. For instance, databases which have fewer repetitions of objects or those systems which are intended to recognize signals with time constraints or capture all data objects. Greater efficiency in processing a relational database can be obtained because the rules for comparison are selected for the maximum efficiency of the processing hardware and/or software, whether or not the processing is based on psychoacoustic or psychovisual models. The benefits of massive data reduction, flexibility in constructing appropriate signal recognition protocols and incorporation of cryptographic techniques to further add accuracy and confidence in the system are clearly improvements over the art. For example, where the data reduced abstract needs to have further uniqueness, a hash or signature may be required. And for objects which have further uniqueness requirements, two identical instances of the object could be made unique with cryptographic techniques.

Accuracy in processing and identification may be increased by using one or more of the following fidelity evaluation functions:

- 1) RMS (root mean square). For example, a RMS function may be used to assist in determining the distance between data based on mathematically determinable Euclidean distance between the beginning and end data points (bits) of a particular signal carrier.
- 2) Frequency weighted RMS. For example, different weights may be applied to different frequency components of the carrier signal before using RMS. This selective weighting can assist in further distinguishing the distance between beginning and end points of the

BLU000009

US 7,346,472 B1

11

signal carrier (at a given point in time, described as bandwidth, or the number of total bits that can be transmitted per second) and may be considered to be the mathematical equivalent of passing a carrier signal difference through a data filter and figuring the average power in the output carrier.

- 3) Absolute error criteria, including particularly the NULL set (described above) The NULL may be utilized in two significant cases: First, in instances where the recognized signal appears to be an identified object which is inaccurately attributed or identified to an object not handled by the database of objects; and second, where a collision of data occurs. For instance, if an artist releases a second performance of a previously recorded song, and the two performances are so similar that their differences are almost imperceptible, then the previously selected criteria may not be able to differentiate the two recordings. Hence, the database must be "recalibrated" to be able to differentiate these two versions. Similarly, if the system identifies not one, but two or more, matches for a particular search, then the database may need "recalibration" to further differentiate the two objects stored in the database.
- 4) Cognitive Identification. For example, the present invention may use an experience-based analysis within a recognition engine. Once such analysis may involve mathematically determining a spectral transform or its equivalent of the carrier signal. A spectral transform enables signal processing and should maintain, for certain applications, some cognitive or perceptual relationship with the original analog waveform. As a novel feature to the present invention, additional classes may be subject to humanly-perceptible observation. For instance, an experience-based criteria which relates particularly to the envisioned or perceived accuracy of the data information object as it is used or applied in a particular market, product, or implementation. This may include a short 3 second segment of a commercially available and recognizable song which is used for commercials to enable recognition of the good or service being marketed. The complete song is marketed as a separately valued object from the use of a discrete segment of the song (that may be used for promotion or marketing—for the complete song or for an entirely different good or service). To the extent that an owner of the song in question is able to further enable value through the licensing or agreement for use of a segment of the original signal, cognitive identification is a form of filtering to enable differentiations between different and intended uses of the same or subset of the same signal (object). The implementation relating specifically, as disclosed herein, to the predetermined identification or recognition means and/or any specified relationship with subsequent use of the identification means can be used to create a history as to how often a particular signal is misidentified, which history can then be used to optimize identification of that signal in the future. The difference between use of an excerpt of the song to promote a separate and distinct good or service and use of the excerpt to promote recognition of the song itself (for example, by the artist to sell copies of the song) relates informationally to a decision based on recognized and approved use of the song. Both the song and applications of the song in its entirety or as a subset are typically based on agreement by the creator and the sender who seeks to utilize the work. Trust in the means for identification, which can be weighted in

12

the present invention (for example, by adjusting bit-addressable information), is an important factor in adjusting the monitoring or recognition features of the object or carrier signal, and by using any misidentification information, (including any experience-based or heuristic information), additional features of the monitored signal can be used to improve the performance of the monitoring system envisioned herein. The issue of central concern with cognitive identification is a greater understanding of the parameters by which any given object is to be analyzed. To the extent that a creator chooses varying and separate application of his object, those applications having a cognitive difference in a signal recognition sense (e.g., the whole or an excerpt), the system contemplated herein includes rules for governing the application of bit-addressable information to increase the accuracy of the database.

- 5) Finally, the predetermined parameters that are associated with a discrete case for any given object will have a significant impact upon the ability to accurately process and identify the signals. For example, if a song is transmitted over a FM carrier, then one skilled in the art will appreciate that the FM signal has a predetermined bandwidth which is different from the bandwidth of the original recording, and different even from song when played on an AM carrier, and different yet from a song played using an 8-bit Internet broadcast. Recognition of these differences, however, will permit the selection of an identification means which can be optimized for monitoring a FM broadcasted signal. In other words, the discreteness intended by the sender is limited and directed by the fidelity of the transmission means. Objects may be cataloged and assessing with the understanding that all monitoring will occur using a specific transmission fidelity. For example, a database may be optimized with the understanding that only AM broadcast signals will be monitored. For maximum efficiency, different data bases may be created for different transmission channels, e.g., AM broadcasts, FM broadcasts, Internet broadcasts, etc.

For more information on increasing efficiencies for information systems, see *The Mathematical Theory of Communication* (1948), by Shannon.

Because bandwidth (which in the digital domain is equated to the total number of bits that can be transmitted in a fixed period of time) is a limited resource which places limitations upon transmission capacity and information coding schemes, the importance of monitoring for information objects transmitted over any given channel must take into consideration the nature and utilization of a given channel. The supply and demand of bandwidth will have a dramatic impact on the transmission, and ultimately, upon the decision to monitor and recognize signals. A discussion of this is found in a co-pending application by the inventor under U.S. patent application Ser. No. 08/674,726 "Exchange Mechanisms for Digital Information Packages with Bandwidth Securitization, Multichannel Digital Watermarks, and Key Management" (which application is incorporated herein by reference as if fully set forth herein).

If a filter is to be used in connection with the recognition or monitoring engine, it may be desirable for the filter to anticipate and take into consideration the following factors, which affect the economics of the transmission as they relate to triggers for payment and/or relate to events requiring audits of the objects which are being transmitted: 1) time of transmission (i.e., the point in time when the transmission

BLU000010

US 7,346,472 B1

13

occurred), including whether the transmission is of a live performance); 2) location of transmission (e.g., what channel was used for transmission, which usually determines the associated cost for usage of the transmission channel); 3) the point of origination of the transmission (which may be the same for a signal carrier over many distinct channels); and 4) pre-existence of the information carrier signal (pre-recorded or newly created information carrier signal, which may require differentiation in certain markets or instances).

In the case of predetermined carrier signals (those which have been recorded and stored for subsequent use), “positional information carrier signals” are contemplated by this invention, namely, perceptual differences between the seemingly “same” information carrier that can be recognized as consumers of information seek different versions or quality levels of the same carrier signal. Perceptual differences exist between a song and its reproduction from a CD, an AM radio, and an Internet broadcast. To the extent that the creator or consumer of the signal can define a difference in any of the four criteria above, means can be derived (and programmed for selectability) to recognize and distinguish these differences. It is, however, quite possible that the ability to monitor carrier signal transmission with these factors will increase the variety and richness of available carrier signals to existing communications channels. The differentiation between an absolute case for transmission of an object, which is a time dependent event, for instance a live or real time broadcast, versus the relative case, which is prerecorded or stored for transmission at a later point in time, creates recognizable differences for signal monitoring.

The monitoring and analysis contemplated by this invention may have a variety of purposes, including, for example, the following: to determine the number of times a song is broadcast on a particular radio broadcast or Internet site; to control security through a voice-activated security system; and to identify associations between a beginner’s drawing and those of great artists (for example to draw comparisons between technique, compositions, or color schemes). None of these examples could be achieved with any significant degree of accuracy using a text-based analysis. Additionally, strictly text-based systems fail to fully capture the inherent value of the data recognition or monitoring information itself.

SAMPLE EMBODIMENTS

In order to better appreciate and understand the present invention, the following sample embodiments are provided. These sample embodiments are provided for exemplary purposes only, and in no way limit the present invention.

Sample Embodiment 1

A database of audio signals (e.g., songs) is stored or maintained by a radio station or Internet streaming company, who may select a subset of the songs are stored so that the subset may be later broadcast to listeners. The subset, for example, may comprise a sufficient number of songs to fill 24 hours of music programming (between 300 or 500 songs). Traditionally, monitoring is accomplished by embedding some identifier into the signal, or affixing the identifier to the signal, for later analysis and determination of royalty payments. Most of the traditional analysis is performed by actual persons who use play lists and other statistical approximations of audio play, including for example, data obtained through the manual (i.e., by persons) monitoring of a statistically significant sample of stations

14

and transmission times so that an extrapolation may be made to a larger number of comparable markets.

The present invention creates a second database from the first database, wherein each of the stored audio signals in the first database is data reduced in a manner that is not likely to reflect the human perceptual quality of the signal, meaning that a significantly data-reduced signal is not likely to be played back and recognized as the original signal. As a result of the data reduction, the size of the second database (as measured in digital terms) is much smaller than the size of the first database, and is determined by the rate of compression. If, for example, if 24 hours worth of audio signals are compressed at a 10,000:1 compression rate, the reduced data could occupy a little more than 1 megabyte of data. With such a large compression rate, the data to be compared and/or analyzed may become computationally small such that computational speed and efficiency are significantly improved.

With greater compression rates, it is anticipated that similarity may exist between the data compressed abstractions of different analog signals (e.g., recordings by two different artists of the same song). The present invention contemplates the use of bit-addressable differences to distinguish between such cases. In applications where the data to be analyzed has higher value in some predetermined sense, cryptographic protocols, such as a hash or digital signature, can be used to distinguish such close cases.

In a preferred embodiment, the present invention may utilize a centralized database where copies of new recordings may be deposited to ensure that copyright owners, who authorize transmission or use of their recordings by others, can independently verify that the object is correctly monitored. The rules for the creator himself to enter his work would differ from a universally recognized number assigned by an independent authority (say, ISRC, ISBN for recordings and books respectively). Those skilled in the art of algorithmic information theory (AIT) can recognize that it is now possible to describe optimized use of binary data for content and functionality. The differences between objects must relate to decisions made by the user of the data, introducing subjective or cognitive decisions to the design of the contemplated invention as described above. To the extent that objects can have an optimized data size when compared with other objects for any given set of objects, the algorithms for data reduction would have predetermined flexibility directly related to computational efficiency and the set of objects to be monitored. The flexibility in having transparent determination of unique signal abstracts, as opposed to independent third party assignment, is likely to increase confidence in the monitoring effort by the owners of the original signals themselves. The prior art allows for no such transparency to the copyright creators.

Sample Embodiment 2

Another embodiment of the invention relates to visual images, which of course, involve at least two dimensions.

Similar to the goals of a psychoacoustic model, a psychovisual model attempts to represent a visual image with less data, and yet preserve those perceptual qualities that permit a human to recognize the original visual image. Using the very same techniques described above in connection with an audio signal, signal monitoring of visual images may be implemented.

One such application for monitoring and analyzing visual images involves a desire to find works of other artists that relate to a particular theme. For example, finding paintings

BLU000011

US 7,346,472 B1

15

of sunsets or sunrises. A traditional approach might involve a textual search involving a database wherein the works of other artists have been described in writing. The present invention, however, involves the scanning of an image involving a sun, compressing the data to its essential characteristics (i.e., those perceptual characteristics related to the sun) and then finding matches in a database of other visual images (stored as compressed or even uncompressed data). By studying the work of other artists using such techniques, a novice, for example, could learn much by comparing the presentations of a common theme by different artists.

Another useful application involving this type of monitoring and analyzing is the identification of photographs of potential suspects whose identity matches the sketch of a police artist.

Note that combinations of the monitoring techniques discussed above can be used for audio-visual monitoring, such as video-transmission by a television station or cable station. The techniques would have to compensate, for example, for a cable station that is broadcasting a audio channel unaccompanied by video.

Other embodiments and uses of the invention will be apparent to those skilled in the art from consideration of the specification and practice of the invention disclosed herein. The specification and examples should be considered exemplary only with the true scope and spirit of the invention indicated by the following claims. As will be easily understood by those of ordinary skill in the art, variations and modifications of each of the disclosed embodiments can be easily made within the scope of this invention as defined by the following claims.

What is claimed is:

1. A method for monitoring and analyzing at least one signal comprising:

receiving at least one reference signal to be monitored;
creating an abstract of said at least one reference signal wherein the step of creating an abstract of said at least one reference signal comprises:
inputting the reference signal to a processor;
creating an abstract of the reference signal using perceptual qualities of the reference signal such that the abstract retains a perceptual relationship to the reference signal from which it is derived;
storing the abstract of said at least one reference signal in a reference database;
receiving at least one query signal to be analyzed;
creating an abstract of said at least one query signal wherein the step of creating an abstract of said at least one query signal comprises:
inputting the at least one query signal to the processor;
creating an abstract of the at least one query signal using perceptual qualities of the at least one query signal such that the abstract retains a perceptual relationship to the at least one query signal from which it is derived; and
comparing the abstract of said at least one query signal to the abstract of said at least one reference signal to determine if the abstract of said at least one query signal matches the abstract of said at least one reference signal.

2. The method of claim 1, wherein the step of creating an abstract of said at least one reference signal comprises:
using a portion of said at least one reference signal to create an abstract of said at least one reference signal; and
the step of creating an abstract of said at least one query signal comprises:

16

using a portion of said at least one query signal to create an abstract of said at least one query signal.

3. A method for monitoring and analyzing at least one signal comprising:

receiving at least one reference signal to be monitored;
creating an abstract of said at least one reference signal;
storing the abstract of said at least one reference signal in a reference database;

receiving at least one query signal to be analyzed;
creating an abstract of said at least one query signal;
comparing the abstract of said at least one query signal to the abstract of said at least one reference signal to determine if the abstract of said at least one query signal matches the abstract of said at least one reference signal;

creating at least one counter corresponding to one of said at least one reference signals, said at least one counter being representative of the number of times a match is found between the abstract of said at least one query signal and the abstract of said at least one reference signal; and

incrementing the counter corresponding to a particular reference signal when a match is found between an abstract of said at least one query signal and the abstract of the particular reference signal.

4. The method of claim 3 further comprising:

recording an occurrence of a match between the abstract of said at least one query signal and the abstract of said at least one reference signal; and

generating a report that identifies the reference signal whose abstract matched the abstract of said at least one query signal.

5. The method of claim 4, further comprising:

recording an occurrence of a match between the abstract of said at least one query signal and the abstract of said at least one reference signal.

6. A method for monitoring a plurality of reference signals, comprising:

creating an abstract for each of the plurality of reference signals wherein the step of creating an abstract for each of a plurality of reference signals comprises:

inputting each of the plurality of reference signals to a processor;

creating an abstract of each one of the plurality of reference signals using perceptual qualities of each one of a plurality of reference signals such that the abstract retains a perceptual relationship to the reference signal from which it is derived;

storing each of said abstracts in a reference database;

receiving at least one query signal to be analyzed;

creating an abstract of each of the at least one query signals wherein the step of creating an abstract of each of the at least one query signals comprises:

inputting each of the at least one query signals to a processor;

creating an abstract of each one of a plurality of reference signals using perceptual qualities of each one of a plurality of reference signals such that the abstract retains a perceptual relationship to the reference signal from which it is derived;

locating an abstract in the reference database that matches the abstract of each at least one query signal; and

recording the identify of the reference signal whose abstract matched the abstract of each at least one query signal.

BLU000012

US 7,346,472 B1

17

7. The method of claim 6, wherein the step of creating an abstract of said at least one reference signal comprises:
using a portion of said at least one reference signal to create an abstract of said at least one reference signal;
and the step of creating an abstract of said at least one query signal comprises:
using a portion of said at least one query signal to create an abstract of said at least one query signal.

8. A method for monitoring a plurality of reference signals, comprising:
creating an abstract for each of the plurality of reference signals;
storing each of said abstracts in a reference database;
receiving at least one query signal to be analyzed;
creating an abstract of each of the at least one query signals;
locating an abstract in the reference database that matches the abstract of each at least one query signal;
recording the identify of the reference signal whose abstract matched the abstract of each at least one query signal;
creating at least one counter corresponding to one of said plurality of reference signals, said at least one counter being representative of the number of times a match is found between the abstract of said at least one query signal and an abstract of one of said plurality of reference signals; and
incrementing the counter corresponding to a particular reference signal when a match is found between an abstract of said at least one query signal and the abstract of the particular reference signal.

9. A computerized system for monitoring and analyzing at least one signal:
a processor that creates an abstract of a signal using selectable criteria;
a first input that receives at least one reference signal to be monitored, said first input being coupled to said processor such that said processor may generate an abstract for each reference signal input to said processor;
a reference database, coupled to said processor, that stores abstracts of each at least one reference signal;
a second input that receives at least one query signal to be analyzed, said second input being coupled to said processor such that said processor may generate an abstract for each query signal;
a comparing device, coupled to said reference database and to said second input, that compares an abstract of said at least one query signal to the abstracts stored in the reference database to determine if the abstract of said at least one query signal matches any of the stored abstracts;
a storage medium coupled to said first input, that stores each of said at least one reference signals to be monitored; and
a controller coupled to the first input, the processor, the comparing device, the reference database and the storage medium, said controller causing an abstract for each reference signal being input for the first time to be compared to all previously stored abstracts in the reference database, such that in the event that the comparing device determines that it cannot distinguish between the abstract of a reference signal being input for the first time from a previously stored abstract in the reference database, the controller adjusts the criteria

18

being used by the processor and re-generates the reference database, by re-processing each reference signal stored on the storage medium to create new abstracts and storing said new abstracts in the reference database.

10. The system of claim 9, wherein the controller includes a means to adjust compression rates at which the processor processes a signal to create an abstract.

11. A computerized system for monitoring and analyzing at least one signal:
a processor that creates an abstract of a signal using selectable criteria;
a first input that receives at least one reference signal to be monitored, said first input being coupled to said processor such that said processor may generate an abstract for each reference signal input to said processor;
a reference database, coupled to said processor, that stores abstracts of each at least one reference signal;
a second input that receives at least one query signal to be analyzed, said second input being coupled to said processor such that said processor may generate an abstract for each query signal;
a comparing device, coupled to said reference database and to said second input, that compares an abstract of said at least one query signal to the abstracts stored in the reference database to determine if the abstract of said at least one query signal matches any of the stored abstracts, wherein the comparing device identifies at least two abstracts in the reference database that match the abstract of said at least one query signal and an index of relatedness to said at least one query signal for each of said at least two matching abstracts.

12. The system of claim 11, further comprising:
a security controller that controls access to a secured area, such that access is granted only if the comparing device confirms that an abstract of said at least one query signal matches an abstract of said at least one reference signal.

13. The system of claim 11, further comprising:
a recorder that records the identify of the reference signal whose abstract matched the abstract of said at least one query signal; and
a report generator that generates a report that identifies the reference signals whose abstracts matched the abstract of said at least one query signal.

14. A electronic system for monitoring and analyzing at least one signal, comprising:
a first input that receives at least one reference signal to be monitored,
a first processor that creates an abstract of each reference signal input to said first processor through said first input;
a second input that receives at least one query signal to be analyzed,
a second processor that creates an abstract of each query signal;
a reference database that stores abstracts of each at least one reference signal;
a comparing device that compares an abstract of said at least one query signal to the abstracts stored in the reference database to determine if the abstract of said at least one query signal matches any of the stored abstracts;
a storage medium coupled to said first input, that stores each of said at least one reference signals to be monitored; and

BLU000013

US 7,346,472 B1

19

a controller that compares an abstract for each reference
signal being input for the first time to be compared to
all previously stored abstracts in the reference database,
such that in the event that the comparing device deter-
mines that it cannot distinguish between the abstract of 5
a reference signal being input for the first time from a
previously stored abstract in the reference database, the

20

controller adjusts the criteria being used by the proces-
sor and re-generates the reference database, by re-
processing each reference signal stored on the storage
medium to create new abstracts and storing said new
abstracts in the reference database.

* * * * *

BLU000014